

DF-380 Parts Washer Compound



DF-380 is an alkaline liquid cleaning compound. It is formulated to penetrate, lift and suspend a wide range of difficult soils and particulate from ferrous metals. This product is designed to work in soak tank and ultra-sonic cleaning systems, and specific turbo washer applications. It is especially good at dispersing particulate type soils and metallic fines.

USAGE & DILUTION RECOMMENDATIONS

Usage range varies from 3 to 6 ounces per gallon. Cleaning solution temperatures should be maintained between 80° and 170° F.

PHYSICAL PROPERTIES

Appearance	Orange liquid
pH @ 1% solution	12.3
Odor	Mild
Foaming action	Moderate
Solubility in water	Complete
Rinsing action	Excellent
Metal Safety	Ferrous
Metals	
Flash point	None
Specific Gravity	1.15
Stability	Stable

HANDLING & STORAGE

This is a highly alkaline product. Use good industrial hygiene practices such as wearing chemical safety goggles, rubber gloves, impermeable apron, and other appropriate safety precautions so as to prevent personal contact with this product and its solutions. Wash thoroughly after handling. In case of skin or eye contact, flush with plenty of water for at least 15 minutes, removing contaminated clothing and shoes. Always contact physician in case of eye contact or if irritation develops or persists after skin contact. Store in tightly closed container and rotate stock. When stored as stated above, shelf life is a minimum of 2 years.

Progress Chemical guarantees its products will perform to your satisfaction when used in accordance to our recommendations. We back this guarantee with over 50 years experience. Our company has been certified to ISO 9001:2000 Quality Standards

.Refer to our Material Safety Data Sheet for additional information

Rev. 12/03



3015 Dormax S.W. Grandville, MI 49418
Phone (616-534-6103 Fax: 534-0920
www.progresschemical.com