

L-310C Parts Washer Compound



L-310C is a heavy duty cleaning compound. It is used for removing a wide range of especially difficult soils from ferrous metals in automated spray wash applications. This product was formulated specifically to give the operator more flexibility in concentration adjustment to allow for an operations particular soil conditions.

PHYSICAL PROPERTIES

| | |
|---------------------|---------------------|
| Appearance | Blue liquid |
| pH @ 1% solution | 12.48 |
| Odor | Mild |
| Foaming action | Low |
| Solubility in water | Complete |
| Rinsing action | Excellent |
| Metal Safety | Ferrous Metals Only |
| Flash point | None |
| Specific Gravity | 1.15 |
| Stability | Stable |
| Standard Container | 55 Gallon drum |

Progress Chemical guarantees its products will perform to your satisfaction when used in accordance to our recommendations. We back this guarantee with over 50 years experience. Our company has been certified to ISO 9001:2000 Quality Standards.

USAGE & DILUTION RECOMMENDATIONS

For use in spray washer applications use 1 to 3 ounces per gallon of water. Solution operating temperature should be maintained between 120° and 170° F. to maintain optimum cleaning and foaming characteristics.

HANDLING & STORAGE

This is a highly alkaline product containing Potassium Hydroxide. Use good industrial hygiene practices such as wearing chemical safety goggles, rubber gloves, impermeable apron, and other appropriate protective clothing to prevent personal contact. Wash thoroughly after handling this product. In case of skin or eye contact, flush with plenty of water for at least 15 minutes and call physician. Store product in tightly closed containers between 50° and 85° F. When stored as stated above, shelf life is a minimum of 2 years.

Refer to our Material Safety Data Sheet for additional information.

Rev. 12/03



3015 Dormax S.W. Grandville, MI 49418
Phone (616-534-6103 Fax: 534-0920
www.progresschemical.com