


L-351E Parts Washer Compound



L-351E is a potent high alkaline liquid cleaning compound able to handle the rigors of heavy soil loads, including chlorinated, and sulfonated oils. It incorporates a special low-foaming cleaning system for cleaning ferrous metals in high pressure spray application parts washers. This product incorporates a non-nitrite inhibitor for interim process corrosion protection and is also silicated.

PHYSICAL PROPERTIES

Appearance	Straw colored liquid
pH @ 1% solution	13.4
Foaming Action	Very low
Rinsing Action	Excellent
Odor	Mild
Metal safety	Ferrous Metals
Flash point	None
Specific Gravity	1.15
Standard Containers	55 Gal. drums

Progress Chemical guarantees its products will perform to your satisfaction when used in accordance to our recommendations. We back this guarantee with over 50 years experience. Our company has been certified to ISO 9001:2000 Quality Standards.

Refer to our Material Safety Data Sheet for additional information.

USAGE AND DILUTION INSTRUCTIONS

Use 2 to 5 ounces of this product per gallon of water used. The amount of product used will depend on specific operation, oils and/or soils to be removed, and operating pressures and characteristics of equipment used. In general, foaming characteristics of this cleaner are reduced under the following conditions: increased temperatures of solution, increased concentration of compound, or increased pH of solution. Maintain operating temperature between 120° - 150°F. If excess foaming occurs check to see if temperature and product concentrations are in accordance to above specifications

HANDLING AND STORAGE INSTRUCTIONS

This is a highly alkaline product containing Potassium Hydroxide and Sodium Metasilicate. Use good industrial hygiene practices such as wearing chemical safety goggles, rubber gloves, impermeable apron, and other appropriate protective clothing to prevent personal contact. Wash thoroughly after handling this product. In case of skin or eye contact, flush with plenty of water for at least 15 minutes and call physician. Due to the high alkaline nature of this product, it should not be used on non-ferrous metals, as it may damage them. Store product in tightly closed containers between 50° and 85° F. When stored as stated above, shelf life is a minimum of 2 years. Rotate stock.

Rev. 12-03



3015 Dormax S.W. Grandville, MI 49418
Phone (616-534-6103 Fax: 534-0920
www.progresschemical.com